

Technical drawing of a DS-25 Spacer for rotor 0.1 mm. The drawing includes a top view, a side view, and a 3D perspective view. Dimensions are specified in millimeters with tolerances.

**Top View Dimensions:**

- Outer Diameter:  $\phi 7.35 \begin{smallmatrix} 0 \\ -0.05 \end{smallmatrix}$
- Inner Diameter:  $\phi 6 \begin{smallmatrix} +0.05 \\ 0 \end{smallmatrix}$

**Side View Dimensions:**

- Thickness:  $0.100 \pm 0.005$  (stock)

**3D View:** A perspective view of the spacer, showing its ring-like structure.

**Notes:**

- 1) For any incompatibility with the model or missing dimension, please refer to Netzer for clarification.
- 2) Burrs are not allowed
- 3) Packing must prevent physical damage during process storage and shipment

**FOR DS-25-R-03**

**REVISIONS**

ZONE	REV.	DESCRIPTION	DATE	DRAWN	APPROVED
	00	For production	6-Jan-2016	Michael A.	

**Notes:**

The information contained in this drawing is the sole property of Netzer Precision Motion Sensores Ltd. Any reproduction in part or whole without the written permission of Netzer Precision Motion Sensors Ltd. is prohibited. The drawing is confidential, and is the property of Netzer Precision Ltd. It must not be disclosed to a third party without written consent of Netzer Precision Ltd.

NAME	SIGNATURE	DATE
DRAWN Michael A.		06-01-16
CHK'D Jacob H.		06-01-16
APPV'D Jacob H.		06-01-16

**UNLESS OTHERWISE SPECIFIED:**  
DIMENSIONS ARE IN mm  
SURFACE FINISH: N6  
LINEAR TOLERANCES:  $\pm 0.1$  mm  
ANGULAR TOLERANCES:  $\pm 0.5$  deg  
ALL CHAMFER: 0.1 mm X 45°

**TITLE: DS-25 Spacer for rotor 0.1 mm**

MATERIAL:	Stainless Steel 302	Coating:		SCALE: 20:1
DWG NO.:	MP-03503-00	Revision:	00	A3
CAT NO.:	MP-03503-00			SHEET 1 OF 1

1 2 3 4 5 6 7 8

A

B

C

D

E

F

REVISIONS					
ZONE	REV.	DESCRIPTION	DATE	DRAWN	APPROVED
	00	For production	6-Jan-2016	Michael A.	

$\phi 7.35 \begin{smallmatrix} 0 \\ -0.05 \end{smallmatrix}$

$\phi 6 \begin{smallmatrix} +0.05 \\ 0 \end{smallmatrix}$

0.100  $\pm$ 0.005 (stock)

Notes:

- 1) For any incompatibility with the model or missing dimension, please refer to Netzer for clarification.
- 2) Burrs are not allowed
- 3) Packing must prevent physical damage during process storage and shipment

FOR DS-25-R-03

The information contained in this drawing is the sole property of Netzer Precision Motion Sensores Ltd. Any reproduction in part or whole without the written permission of Netzer Precision Motion Sensors Ltd.is prohibited. The drawing is confidential,and is the property of Netzer Precision Ltd. it must not be disclosed to a third party without written consent of Netzer Precision Ltd.

	NAME	SIGNATURE	DATE
DRAWN	Michael A.		06-01-16
CHK'D	Jacob H.		06-01-16
APPV'D	Jacob H.		06-01-16

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN mm  
SURFACE FINISH: N6  
LINEAR TOLERANCES:  $\pm$ 0.1 mm  
ANGULAR TOLERANCES:  $\pm$ 0.5 deg  
ALL CHAMFER: 0.1 mm X 45°

TITLE: **DS-25 Spacer for rotor 0.1 mm**

MATERIAL: Stainless Steel 302

DWG NO.: MP-03503-00

CAT NO.: MP-03503-00

Coating:

Revision : 00

SCALE: 20:1

A3

SHEET 1 OF 1

1 2 3 4 5 6 7 8

A

B

C

D

E

F

REVISIONS					
ZONE	REV.	DESCRIPTION	DATE	DRAWN	APPROVED
	00	For production	6-Jan-2016	Michael A.	

$\phi 7.35 \begin{smallmatrix} 0 \\ -0.05 \end{smallmatrix}$

$\phi 6 \begin{smallmatrix} +0.05 \\ 0 \end{smallmatrix}$


0.100 ±0.005 (stock)

FOR DS-25-R-03

Notes:  
1) For any incompatibility with the model or missing dimension, please refer to Netzer for clarification.  
2) Burrs are not allowed  
3) Packing must prevent physical damage during process storage and shipment

The information contained in this drawing is the sole property of Netzer Precision Motion Sensores Ltd. Any reproduction in part or whole without the written permission of Netzer Precision Motion Sensors Ltd.is prohibited. The drawing is confidential,and is the property of Netzer Precision Ltd. it must not be disclosed to a third party without written consent of Netzer Precision Ltd.

	NAME	SIGNATURE	DATE
DRAWN	Michael A.		06-01-16
CHK'D	Jacob H.		06-01-16
APPV'D	Jacob H.		06-01-16



**Netzer**  
Precision Motion Sensors Ltd.

**TITLE: DS-25 Spacer for rotor 0.1 mm**

MATERIAL: Stainless Steel 302


DWG NO.: MP-03503-00

CAT NO.: MP-03503-00

Coating:

Revision :

00

SCALE: 20:1

A3

SHEET 1 OF 1

1 2 3 4 5 6 7 8

A

B

C

D

E

F

REVISIONS					
ZONE	REV.	DESCRIPTION	DATE	DRAWN	APPROVED
	00	For production	6-Jan-2016	Michael A.	

$\phi 7.35 \begin{smallmatrix} 0 \\ -0.05 \end{smallmatrix}$

$\phi 6 \begin{smallmatrix} +0.05 \\ 0 \end{smallmatrix}$

0.100 ±0.005 (stock)

Notes:

- 1) For any incompatibility with the model or missing dimension, please refer to Netzer for clarification.
- 2) Burrs are not allowed
- 3) Packing must prevent physical damage during process storage and shipment

FOR DS-25-R-03

The information contained in this drawing is the sole property of Netzer Precision Motion Sensores Ltd. Any reproduction in part or whole without the written permission of Netzer Precision Motion Sensors Ltd.is prohibited. The drawing is confidential,and is the property of Netzer Precision Ltd. it must not be disclosed to a third party without written consent of Netzer Precision Ltd.

	NAME	SIGNATURE	DATE
DRAWN	Michael A.		06-01-16
CHK'D	Jacob H.		06-01-16
APPV'D	Jacob H.		06-01-16

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN mm  
SURFACE FINISH: N6  
LINEAR TOLERANCES: ±0.1 mm  
ANGULAR TOLERANCES: ±0.5 deg  
ALL CHAMFER: 0.1 mm X 45°

TITLE: **DS-25 Spacer for rotor 0.1 mm**

MATERIAL: Stainless Steel 302

DWG NO.: MP-03503-00

CAT NO.: MP-03503-00

Coating:

Revision : 00

SCALE: 20:1

A3

SHEET 1 OF 1